

PS9P2

PS9P4

PS9P3

# ElettroMagnetic Services

SRL

## POWER SPLITTER

- Two, three and four ports versions
- Low VSWR and insertion loss
- Other bands and/or connectors available upon request

PS12P2



PS12P3



PS12P4



## ELECTRICAL

Frequency	3400 ÷ 3600 MHz	(PS9P2)
	3400 ÷ 3600 MHz	(PS9P3)
	3400 ÷ 3600 MHz	(PS9P4)
Impedance in/out	50 Ω	
Number of output ports	2	(PS9P2)
	3	(PS9P3)
	4	(PS9P4)
VSWR across band	≤ 1.25	
Insertion loss	< 0.3 dB	
Max. amplitude unbalance at output ports	< 0.4 dB	(PS9P2)
	< 0.5 dB	(PS9P3)
	< 0.5 dB	(PS9P4)
Max. phase unbalance at output ports	< 5°	(PS9P2)
	< 10°	(PS9P3)
	< 15°	(PS9P4)
Power rating	10 W cw	

## MECHANICAL

Input connector	N-male	
Output connectors	N-female	
Dimensions (W×H×D)	53 × 38 × 31 mm	(PS9P2)
	92 × 38 × 31 mm	(PS9P3)
	111 × 60 × 31 mm	(PS9P4)
Mass	180 g	(PS9P2)
	240 g	(PS9P3)
	330 g	(PS9P4)
Standard finish	aluminium diecast enclosure, RAL7035 (light grey) painted	
IP protection grade	IP 54	

Due to technical improvements, specifications provided in this data sheet may change without notice. Whilst every effort is made to ensure an high degree of accuracy to all specifications here reported, no responsibility can be accepted for any errors or omissions. Any reproduction, full or partial, of this document and its contents is not allowed without factory authorization.

Since **ElettroMagnetic Services** is specialized in development and production of custom antennas, if you need electrical and/or mechanical modifications of this product to meet a particular application or requirements, please feel free to contact us directly.

## HEADQUARTERS

**ElettroMagnetic Services srl**

via S. Pertini, 6  
26019 VAILATE (CR) - ITALY

Tel +39 (0) 363 84086

Fax +39 (0)363 341636

Email [info@elettromagneticservices.com](mailto:info@elettromagneticservices.com)

Issued: 26.05.09  
Updated: 04.11.16